

## **AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

### **LISTING OF CLAIMS:**

1. (currently amended) A sprinkling device, ~~particularly for processes for making wine from red grapes, which device can be~~ associated with a fermentation and/or storage tank in order to recirculate the wine must that is being fermented from the base region to the top region of the fermentation tank and to sprinkle the recirculated wine must in a stream into the top region of the fermentation tank, said sprinkling device comprising:

- an auxiliary tank ~~which can be fitted in a hatch or similar top opening of a main~~ fermentation tank and which is provided with means for fixing to the hatch,

- first discharge means for ~~the discharge of~~ discharging the wine must that is supplied to the auxiliary tank from the ~~main~~ fermentation tank, ~~which said first discharge means comprise comprising~~ an opening in the base of the auxiliary tank and a closure member which is movable between a closure position and an open position in order to produce a first sprinkling stream of the recirculated wine must, and

- second discharge means for ~~the discharge of~~ discharging the wine must, ~~which means are~~ said second discharge means being associated with the closure member and can discharge the wine must by means of a second sprinkling stream when the level of recirculated wine must in the auxiliary tank reaches a predetermined level,

wherein the second discharge means comprise an auxiliary discharge opening in the closure member and an overflow duct communicating with the opening in order to deliver the recirculated wine must through the auxiliary opening.

2. (Canceled).

Claim 3 (currently amended): A sprinkling device, ~~particularly for processes for~~ making wine from ~~red~~ grapes, which device ~~can be~~ is associated with a fermentation ~~and/or~~ storage tank in order to recirculate the wine must that is being fermented from the base region to the top region of the fermentation tank and to sprinkle the recirculated wine must in a stream into the top region of the fermentation tank, said sprinkling device comprising:

- an auxiliary tank ~~which can be fitted in a hatch or similar top opening of a main~~ the fermentation tank and which is provided with means for fixing to the hatch,

- first discharge means for ~~the discharge of~~ discharging the wine must that is supplied to the auxiliary tank from the ~~main~~ fermentation tank, ~~which said first discharge means comprise~~ comprising an opening in the base of the auxiliary tank and a closure member which is movable between a closure position and an open position in order to produce a first sprinkling stream of the recirculated wine must, and

- second discharge means for ~~the discharge of~~ discharging the wine must, ~~which means~~ are said second discharge means being associated with the closure member and can discharge the

Amendment Under 37 C.F.R. § 1.111  
Serial No.: 10/716,422  
SUGHRUE MION, PLLC Ref: Q78585

wine must by means of a second sprinkling stream when the level of recirculated wine must in the auxiliary tank reaches a predetermined level,

wherein the second discharge means ~~comprise~~ comprises an auxiliary discharge opening and a diffuser member which is associated with the auxiliary discharge opening and which can interfere with the sprinkling stream coming from the opening in order to modify the shape of the stream.

Claim 4 (original): A sprinkling device according to Claim 3, wherein the diffuser member comprises a member with a conical surface associated with the closure member beneath the auxiliary opening.

Claim 5 (original): A sprinkling device according to Claim 3, wherein the diffuser member comprises an inclined plate, associated with the closure member beneath the auxiliary opening and suit-able for producing a directional sprinkling stream.

Claim 6 (currently amended): A sprinkling device according to Claim 1, wherein said auxiliary tank comprises associated supply means for the re-circulated wine must, the supply means being connectible to a recirculation duct which draws off the wine must from the ~~main~~ main fermentation tank with which the device is associated.

Claim 7 (currently amended): A sprinkling device according to Claim 6, wherein said supply means comprise a supply duct connectable to said re-circulation duct, having one or more end nozzles suitable to supply one or more streams of recirculated wine must with a ~~jet(s)~~jet oriented according to pre-determined directions through the base opening of the tank, when the closure member is open.

Claim 8 (currently amended): A sprinkling device, ~~particularly for processes for making wine from red grapes, which device can be~~is associated with a fermentation ~~and/or storage tank~~ in order to recirculate the wine must that is being fermented from the base region to the top region of the fermentation tank and to sprinkle the recirculated wine must in a stream into the top region of the fermentation tank, said sprinkling device comprising:

- an auxiliary tank ~~which can be fitted in a hatch or similar top opening of a main~~the fermentation tank and which is provided with means for fixing to the hatch,

- first discharge means for ~~the discharge of~~discharging the wine must that is supplied to the auxiliary tank from the ~~main~~fermentation tank, ~~which said first discharge means comprise~~comprising an opening in the base of the auxiliary tank and a closure member which is movable between a closure position and an open position in order to produce a first sprinkling stream of the recirculated wine must, and

- second discharge means for ~~the discharge of~~discharging the wine must, ~~which means~~are said second discharge means being associated with the closure member and can discharge the

Amendment Under 37 C.F.R. § 1.111  
Serial No.: 10/716,422  
SUGHRUE MION, PLLC Ref: Q78585

wine must by means of a second sprinkling stream when the level of recirculated wine must in the auxiliary tank reaches a predetermined level,

wherein said auxiliary tank comprises associated supply means for the re-circulated wine must, the supply means being connectible to a recirculation duct which draws off the wine must from the ~~main~~-fermentation tank with which the device is associated; and

wherein the supply means comprise three-way valve means with an inlet connector connectible to the recirculation duct, a first outlet duct which supplies the recirculated wine must into the auxiliary tank through the valve means, and a second outlet duct which is arranged to be connected to a duct for supplying the recirculated wine must to the ~~main~~-fermentation tank, the valve means being arranged to supply the recirculated wine must selectively to the first outlet duct or to the second outlet duct.

Claim 9 (original): A sprinkling device according to Claim 8, comprising oxygenation means, associated with the first outlet duct and/or with the second outlet duct, for oxygenating the recirculated wine must.

Claim 10 (original): A sprinkling device according to Claim 9, wherein the oxygenation means comprise air-injection means.

Amendment Under 37 C.F.R. § 1.111  
Serial No.: 10/716,422  
SUGHRUE MION, PLLC Ref: Q78585

Claim 11 (original): A sprinkling device according to Claim 1, wherein the first discharge means can be operated in order to modulate the head of wine must in the tank in order to determine the width and characteristics of the sprinkling stream.

Claim 12 (original): A sprinkling device according to Claim 11, wherein the first discharge means are actuated by an electric actuator.

Claim 13 (original): A sprinkling device according to Claim 1, wherein the first discharge means comprise a plate-like closure member having, on the side facing towards the interior of the auxiliary tank, an inclined wall suitable for producing an asymmetric, directional sprinkling stream through the base opening of the auxiliary tank.

Claim 14 (original): A sprinkling device according to Claim 1, wherein the first discharge means comprise a plate-like closure member articulated laterally to the wall delimiting the base opening and a rod-like operating member which can bring about inclined angular opening of the closure member in order to produce an asymmetric, directional sprinkling stream.

Claim 15 (original): A sprinkling device according to Claim 1, wherein the first discharge means comprise a plate-like closure member connected to an operating rod, the plate having a peripheral profile which projects asymmetrically beyond the peripheral profile of the base opening in order to produce an asymmetric, directional sprinkling stream.

Amendment Under 37 C.F.R. § 1.111  
Serial No.: 10/716,422  
SUGHRUE MION, PLLC Ref: Q78585

Claim 16 (original): A sprinkling device according to Claim 1, wherein said first discharge means comprise a base opening of said auxiliary tank having a mouth profile lying in an inclined plane with respect to the vertical and a plate closure member connected to an operating rod which can be inclined with respect to the vertical.

Claim 17 (currently amended): Fermentation apparatus comprising ~~a main tank or vat~~the fermentation tank and ~~a~~the sprinkling device according to Claim 1, associated with a ~~hatch or similar~~a top opening of the fermentation tank ~~or vat~~.

Claim 18 (currently amended): Fermentation apparatus according to Claim 17, ~~wherein said fermentation tank or vat has a hatch or similar~~the top opening is positioned in an asymmetric position.

Claim 19 (previously presented): Fermentation apparatus according to Claim 17, comprising recirculation means which are arranged to draw off the wine must from the base region of the main fermentation tank or vat and to supply the wine must into the sprinkling device.

Claim 20 (original): Fermentation apparatus according to Claim 19, wherein the recirculation means comprise pumping means arranged to supply to the sprinkling device a

Amendment Under 37 C.F.R. § 1.111  
Serial No.: 10/716,422  
SUGHRUE MION, PLLC Ref: Q78585

recirculation flow rate such as to produce the second sprinkling stream through the second discharge means even when the first discharge means are in the open position.